



Material Safety Data Sheet

Section 1 - Material Identification

Product: **BA57** Manufacturer: **Master Wall Inc.**
 Address: **6975 Flat Rock Road**
Midland, GA 31820

Date Issued: **9/3/1997 Revised 1/1/10** Telephone: **706-569-0092**
www.masterwall.com

Section 2 - Hazard Ingredients/Identity Information

Ingredients	CAS#	OSHA-PEL	ACGIH-TLV	%
Acrylic Polymer	N/A	NE	NE	
Ammonia		50 ppm	25 ppm	
Aromatic Hydrocarbon		50 ppm	unknown	
2(Hydroxymethyl) aniolethanol		NE	LD=770 mg/kg in rats	
Water	7732-18-5	NE	NE	

Section 3 - Physical/Chemical Characteristics

Boiling Point:	Over 212°F	Specific Gravity (H ₂ O=1):	1.31
Vapor Pressure:	N/A	Melting Point:	N/A
Vapor Density (AIR=1):	Heavier than air	Evaporation Rate (Butyl Acetate=1):	Slower
Solubility in Water:	Dilutable		
Appearance and Odor:	Thin, milky, batter like mixture		

Section 4 - Fire and Explosion Hazard Data

Flash Point (Method Used)	N/A	Flammable Limits: N/A	LEL	UEL
Extinguishing Media:	Class B fire extinguisher. Use foam, carbon dioxide or dry chemicals			
Special Fire Fighting Procedures:	N/A			
Unusual Fire and Explosion Hazards:	Closed container may build up pressure due to heat exposure - containers may rupture or melt.			

Section 5 - Reactivity Data

Stability	Unstable		Conditions to Avoid:	N/A
	Stable	x		
Incompatibility (Materials to Avoid):				
Hazardous Decomposition or Byproducts:				
Hazardous Polymerization	May Occur		Conditions to Avoid:	N/A
	Will Not Occur	x		

Section 6 - Health Hazard Data

Routes of Entry

 Inhalation? Yes

 Skin? No

 Ingestion? Yes

Health Hazards (Acute and Chronic)

Can be eye irritant when atomized

Inhalation: vapors may irritate nose, throat and lungs. May cause headaches and nausea without proper ventilation.

Carcinogenicity: NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure:

See health hazards

Medical Conditions Generally Aggravated by Exposure

Respiratory problems

Emergency and First Aid Procedures

If ingested, give two glasses of water and induce vomiting - consult physician.

Section 7 - Precautions for Safe Handling and Use

Steps to be taken in case material is released or spilled

Contain spill with inert material (sand, absorbent, dirt)

Return spill to containers and dispose

Keep out of sewers and bodies of water

Waste Disposal Method

Reuse uncontaminated leftovers when possible

Dispose of material in accordance to local, state and federal regulations

Precautions to be taken in handling and storing

Do not freeze - may coagulate

Provide sufficient ventilation when applying

Other Precautions

If frozen, thaw at room temperature and avoid breathing vapors. Avoid skin and eye contact also. Do not use after being frozen.

Section 8 - Control Measures

Respiratory Protection (Specify Type)

Not normally required. Limit exposure time, use in open, well ventilated area.

Ventilation

Local Exhaust

 Provide sufficient amt. To maintain exposure below TLV.

Special

Mechanical (General)

Other

Protective Gloves:

 Rubber

Eye Protection:

 Safety Glasses

Other Protective Clothing or Equipment

Use adequate clothing to minimize skin contact

Work/Hygienic Practices

Clean clothing on a regular basis

EPA Supplier Notification/Environmental:

This trade name product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Re-authorization Act of 1986 (SARA) and 40 CFR Part 372.

This product contains no ingredients on the list of Extremely Hazardous Substances for SARA Emergency Planning.

Tier I / Tier II Hazard Category (40 CFR 370): Immediate Health Hazard.

The information contained in this bulletin is based upon data considered accurate and is presented in good faith. Master Wall Inc. assumes no liability, either expressed or implied for personal injury or any other conditions caused by the use of this material.