

Project Submittal Package

Project:

Location:

Architect:

General Contractor:

Applicator:



800.755.0825 | 1 Master Wall Ct. Columbus, GA 31907 | masterwall.com/accent



ACCENT STUCCO FINISH

ACCENT® Stucco Finish is a quality textured finish for use over traditional stucco base, One Coat Stucco (OCS), masonry or concrete surfaces. ACCENT® Stucco Finish is available in four different textures and 64 standard colors.

FEATURES & BENEFITS

- Stucco Grade Finish available in Standard Acrylic and Elastomeric Plus versions
- Dirt Pickup Resistant (DPR) 100% Acrylic Polymers
- Integrally Colored with 64 Standard Colors
- Durable Aggregate
- Mold/Mildew Resistant
- Easily applied to all stucco surfaces

Application Temperature: 40°-110°F (5°-43°C) Working Time: 1/4 hr. Set Time: 8-12 hrs. Dry Time: 48-72 hrs. at room temperature, working and drying time will vary with temperature and humidity.

APPLICATION PROCEDURE

Job Conditions - Air and substrate temperature for application of ACCENT® Stucco Finishes must remain within Application Range for a minimum of 24 hours. Provide temporary protection to protect the wall system from damage until permanent flashings, caps and sealants are installed.

Preparation - The substrate must be approved by Master Wall Inc.®, clean, dry, structurally sound and free of efflorescence, oil, grease, form release agents and curing compounds or anything that would affect bond. Painted surfaces are not acceptable and must be removed. Concrete and surfaces should cure for a minimum of 28 days. Stucco should be cured until clean, dry and hard with a pH of 10 or less (typically 14 days), 13 or less if ACCENT® Primer is used.

Mixing - Thoroughly stir ACCENT® Stucco Finish using a heavy duty 1/2" drill at 400 - 500 rpm and a heavy duty mixing paddle. Small amounts of clean, potable water may be added to obtain a workable consistency. To avoid color variations, add the same amount of water to each pail. Do not exceed 24 ounces (0.7 L) of water per pail of finish.

Application — Apply a uniform thickness (about 1/16", 1.6 mm) of ACCENT® Stucco Finish to the substrate using a stainless steel trowel. Spread evenly and then scrape the finish coat down to a thickness no greater than the largest aggregate in the material. Immediately float the finish coat using a plastic float to the desired texture. Always maintain a wet edge to achieve uniformity of texture and color.

Coverage per pail (sf/sm)*

Accent Stucco Swirl:
110-140 sf/pail (10-13 sm)

Accent Stucco Fine Sand and DuroTex Fine:
160-170 sf/pail (15-15.8 sm)

Accent Stucco Medium Sand and DuroTex Medium:
120-140 sf/pail (11-13 sm)

Accent Stucco Versatex:
Up to 300 sf/pail (27.8 sm)
smooth but varies with texture

**All coverage is approximate and depend upon substrate, details and individual application*

Packaging/Shelf Life/Storage

Packaging: 5 gallon (19 L) pail
Shelf Life: 2 years

Storage: Protect from extreme heat - 90°F (32°C), freezing and direct sunlight.

FOR PROFESSIONAL RESULTS

1. Apply finish coats away from direct sunlight. Cold joints or color variations can occur if the finish dries too quickly.
2. Consider priming stucco surfaces with ACCENT® Primer to even out finish absorption.
3. Surfaces exposed to the weather must be sloped (6:12 minimum recommended).
4. Under certain conditions dark colors may show efflorescence on the surface during the cure process.
5. Finishes are intended for the approved substrates listed above and are not approved for any EIFS installation.

Clean Up—Tools and equipment can be cleaned with soapy water while the ACCENT® Stucco Finish is still wet.

SAFETY

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.



Accent Stucco Swirl



Accent Stucco Fine Sand
Accent DuroTex Fine



Accent Stucco Medium Sand
Accent DuroTex Medium



Accent Stucco Versatex

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2026 Master Wall Inc.®



The Accent logo features a blue square with a white 'A' containing an accent mark, followed by the word 'ACCENT' in white serif font on a black background.

ÁCCENT[®]

The Accent logo features a blue square with a white 'A' containing an accent mark, followed by the word 'ACCENT' in white serif font on a black background.

ÁCCENT[®]


800.755.0825 | 1 Master Wall Ct. Columbus, GA 31907 | masterwall.com/accent

SUPERIOR COLOR SELECTOR




Superior Color Selector


All colors shown here are intended to show approximate color of the finish. Do not use this color chart as the final selection as colors are affected by age, texture, lighting conditions, heat and application processes. Color swatches will vary in color and finish to the actual product due to jobsite conditions and methods of applications.




#420 White



#840 White




#108 Burns White




#143 White Waters




#461 Pampas White



#301 China White



#609 Linen



#101 Polar White



#413 Amarillo White




#206 Natural White



#482 Magnolia White



#406 Silver Fox



#22 Kool



#106 Sky



#505 Pearl Gray



#504 Oyster Gray



#102 Seamist



#340 Mockingbird



#380 Mountain Haze



#368 Driftwood



#360 English Fog



#403 Weathered



#150 Iris



#330 Dove Gray



#310 Ash



#210 London White



#464 Lunar



#104 Clay



#933 Stow



#522 Antique Ivory



#559 Mellow



#611 Flax



#610 Dutch Cream



#400 Creme



#460 Amarillo



#107 Beach Sand



#208 Sandle Beige



#500 Egg



#463 Calvary



#402 Par



#475 Chalk



#473 Truffle



#155 Tripoli Tan



#105 Gillam



#613 Boca Raton



#660 Taupe



#606 Fuzzy Peach



#341 Silky White



#410 Beech



#120 Salmon



#408 Sandlewood



#909 Victorian



#934 Pebble Sand



#180 Beige



#618 Light Beige



#372 Soft Plum



#900 Adobe



#616 Tan



#930 Pink Champagne



#227 Brown



#517 Wooden Oar



#920 Pine Cone



#927 Scarlet Red



#646 Sage

Actual color selection should be made from a 1'x1' sample of each color, texture and finish made by the applicator who is actually completing the project.



PRODUCT DATA

BASE COAT & ADHESIVE

Base Coat & Adhesive is a high-performance, polymer-modified leveling base coat, foam trim adhesive and base coat for Portland cement stucco. Base Coat & Adhesive mixes easily with water its creamy consistency helps true wall surfaces while providing additional weather protection.

MIXING

1. Add 1.5 gallons (5.7 L) of clean, potable water to a clean 5 gallon pail.
2. Slowly add one bag of Base Coat & Adhesive to the water while continuously stirring using a heavy duty 1/2" drill at 400 - 500 rpm and a heavy duty mixing paddle.
3. Mix thoroughly for a minimum of 3 to 5 minutes.
4. Stop mixing and allow the material to take its initial set.
5. Re-temper the material adding only enough water to reach the desired consistency. DO NOT add any more water than prescribed.

APPLICATION

For Use As A Leveling Coat:

1. Apply the material to the area needed to be leveled.
2. Application method will vary due to job conditions. NOTE: Protect applied product from inclement weather until fully cured or finish is applied.

For Use As A Foam Trim Adhesive:

1. Apply the Base Coat & Adhesive to the back of the EPS Insulation Board with a 3/8"x3/8"x3/8" (9.5x9.5x9.5 mm) or a 3/8"x1/2"x1-1/2" (9.5x13x38 mm) stainless steel notched trowel.
2. Apply the Base Coat & Adhesive to the back side of the insulation board.
3. Press the trim piece onto the wall at the desired location.
4. Allow the Base Coat & Adhesive to set for a minimum of 24 hours prior to working on the insulation board.

For Use As A Foam Trim Base Coat:

1. Apply Base Coat & Adhesive to the substrate a minimum of 1/16" (3.2 mm) thick.
2. Completely embed Accent Reinforcing Mesh into the wet skim coat.
3. Trowel smooth, ensuring that no reinforcing mesh color is visible.

Coverage per bag (sf/sm)*

80 ft² to 90 ft² (7.4 m² to 8.4 m²)

**All coverage is approximate and depend upon substrate, details and individual application*

Packaging/Shelf Life/Storage

Base Coat & Adhesive is packaged in its natural gray or white color in moisture resistive, 50 lb. (22.7 kg) bags.

Store bags in a cool, dry location away from direct contact with the ground and/or concrete, out of direct sunlight and protected from weather and other damage.

Area of Use

Base Coat & Adhesive may be applied to the following substrates:

1. Portland Cement/One Coat Stucco
2. Masonry
3. Poured-in-place and/or Tilt-up concrete.
4. Expanded Polystyrene Trim (with Accent Mesh).

Surface Preparation

All surfaces to receive application must be clean, dry and free of debris, dirt and dust, efflorescence, grease, oils, curing agents, paint/coatings and cleaning solutions. Ensure that all surfaces are smooth and free of any irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Cleaning and smoothing may be accomplished by pressure washing, mechanical sanding, scraping, chipping, and/or sand blasting. Smooth or glossy surfaces must be roughened to ensure a proper bond.

Product should fully cure in 7 to 28 days following application. Curing time may vary due to ambient temperature, surface temperature surface porosity, application methods, and/or thickness of material. All freshly applied material must be protected by an approved protective system from inclement weather for a minimum of 24 hours at 70° F (21° C) and 55% R.H. It is the responsibility of the applicator to determine if the product is cured and/or dry prior to exposing it to rain, snow, dew, and/or any other inclement weather condition that may be detrimental to the product. Cover with an approved coating or Accent Stucco Finish as soon as possible.

DO NOT apply product when the ambient and surface temperature is below 40°F/4°C or above 100° F/34° C. The ambient and surface temperature must stay consistently within this range until fully cured (see also CURING). Material that is allowed to freeze may suffer irreparable damage. Protect all work from inclement weather with an approved protective system until fully cured.

DO NOT add any other materials to the mixture of the product without written approval from Master Wall Inc.® deviate in the mixing or application procedures contained in this, or any other ACCENT Data Sheets, without written approval from Master Wall Inc.®

Cleaning may be accomplished with water immediately after use.

WARNING, THIS PRODUCT CONTAINS SILICA

If sanding or scraping are performed, ventilate work area and/or use a NIOSH/MSHA-approved respirator in accordance with our Safety Data Sheet.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2026 Master Wall Inc.®



Health & Safety

WARNING! Causes eye and skin irritation. Precautionary Statement Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Store locked up. Dispose of contents/container in accordance with Local, State, Federal and Provincial regulation.

Spills: Collect with suitable absorbent material such as cotton rags.

Disposal: Dispose of in accordance with local, state or federal regulations.

Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.

Consult the Safety Data Sheet (SDS) in the Products section at masterwall.com for further health and safety information.

LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.



PRODUCT DATA

HARDCOAT MORTAR

Hardcoat Mortar is a high-performance, polymer-modified leveling base coat, foam trim adhesive and base coat for Portland cement stucco. Hardcoat Mortar mixes easily with water its creamy consistency helps true wall surfaces while providing additional weather protection.

MIXING

1. Add 1.5 gallons (5.7 L) of clean, potable water to a clean 5 gallon pail.
2. Slowly add one bag of Hardcoat Mortar to the water while continuously stirring using a heavy duty 1/2" drill at 400 - 500 rpm and a heavy duty mixing paddle.
3. Mix thoroughly for a minimum of 3 to 5 minutes.
4. Stop mixing and allow the material to take its initial set.
5. Re-temper the material adding only enough water to reach the desired consistency. DO NOT add any more water than prescribed.

APPLICATION

For Use As A Leveling Coat:

1. Apply the material to the area needed to be leveled.
2. Application method will vary due to job conditions. NOTE: Protect applied product from inclement weather until fully cured or finish is applied.

For Use As A Foam Trim Adhesive:

1. Apply the Base Coat & Adhesive to the back of the EPS Insulation Board with a 3/8"x3/8"x3/8" (9.5x9.5x9.5 mm) or a 3/8"x1/2"x1-1/2" (9.5x13x38 mm) stainless steel notched trowel.
2. Apply the Hardcoat Mortar to the back side of the insulation board.
3. Press the trim piece onto the wall at the desired location.
4. Allow the Hardcoat Mortar to set for a minimum of 24 hours prior to working on the insulation board.

For Use As A Foam Trim Base Coat:

1. Apply Hardcoat Mortar to the substrate a minimum of 1/16" (3.2 mm) thick.
2. Completely embed Accent Reinforcing Mesh into the wet skim coat.
3. Trowel smooth, ensuring that no reinforcing mesh color is visible.

Coverage per bag (sf/sm)*

80 ft² to 90 ft² (7.4 m² to 8.4 m²)

**All coverage is approximate and depend upon substrate, details and individual application*

Packaging/Shelf Life/Storage

Base Coat & Adhesive is packaged in its natural gray or white color in moisture resistive, 50 lb. (22.7 kg) bags.

Store bags in a cool, dry location away from direct contact with the ground and/or concrete, out of direct sunlight and protected from weather and other damage.

Area of Use

Hardcoat Mortar may be applied to the following substrates:

1. Portland Cement/One Coat Stucco
2. Masonry
3. Poured-in-place and/or Tilt-up concrete.
4. Expanded Polystyrene Trim (with Accent Mesh).

Surface Preparation

All surfaces to receive application must be clean, dry and free of debris, dirt and dust, efflorescence, grease, oils, curing agents, paint/coatings and cleaning solutions. Ensure that all surfaces are smooth and free of any irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Cleaning and smoothing may be accomplished by pressure washing, mechanical sanding, scraping, chipping, and/or sand blasting. Smooth or glossy surfaces must be roughened to ensure a proper bond.

Product should fully cure in 7 to 28 days following application. Curing time may vary due to ambient temperature, surface temperature surface porosity, application methods, and/or thickness of material. All freshly applied material must be protected by an approved protective system from inclement weather for a minimum of 24 hours at 70° F (21° C) and 55% R.H. It is the responsibility of the applicator to determine if the product is cured and/or dry prior to exposing it to rain, snow, dew, and/or any other inclement weather condition that may be detrimental to the product. Cover with an approved coating or Accent Stucco Finish as soon as possible.

DO NOT apply product when the ambient and surface temperature is below 40°F/4°C or above 100° F/34° C. The ambient and surface temperature must stay consistently within this range until fully cured (see also CURING). Material that is allowed to freeze may suffer irreparable damage. Protect all work from inclement weather with an approved protective system until fully cured.

DO NOT add any other materials to the mixture of the product without written approval from Master Wall Inc.® deviate in the mixing or application procedures contained in this, or any other ACCENT Data Sheets, without written approval from Master Wall Inc.®

Cleaning may be accomplished with water immediately after use.

WARNING, THIS PRODUCT CONTAINS SILICA

If sanding or scraping are performed, ventilate work area and/or use a NIOSH/MSHA-approved respirator in accordance with our Safety Data Sheet.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2026 Master Wall Inc.®



Health & Safety

WARNING! Causes eye and skin irritation. Precautionary Statement Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Store locked up. Dispose of contents/container in accordance with Local, State, Federal and Provincial regulation.

Spills: Collect with suitable absorbent material such as cotton rags.

Disposal: Dispose of in accordance with local, state or federal regulations.

Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.

Consult the Safety Data Sheet (SDS) in the Products section at masterwall.com for further health and safety information.

LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.



WISE ADHESIVE & BASE

Vise Adhesive is manufactured with high-grade aggregates and a pure acrylic emulsion binder, field mixed with Type I or I-II Portland cement meeting ASTM C150. Vise Adhesive is intended for use in adhering Expanded Polystyrene (EPS) Insulation Board to an approved substrate, or as a base coat or leveling coat over Portland cement stucco, One Coat Stucco and Brick, masonry or concrete surfaces.

MIXING

1. Thoroughly stir Vise Adhesive using a heavy duty 1/2" (12.7 mm) drill at 400-500 rpm and a heavy duty mixing paddle.
2. Pour half of the stirred Vise Adhesive into a clean plastic pail.
3. Add Type I or I-II Portland cement to the half pail of Vise Adhesive in a ratio of one-to-one by weight and mix to a homogenous consistency.
4. Let the mixture stand for 3 to 5 minutes and then stir to a creamy consistency.
5. Up to 25 ounces (0.7 L) of clean, potable water may be added to a half pail to adjust workability.
6. Do not over mix as faster setting or reduced working time can occur. Do not add accelerators or retarders to the Vise Adhesive mixture.

APPLICATION

For Use As A Leveling Coat:

1. Apply the material to the area needed to be leveled.
2. Application method will vary due to job conditions. NOTE: Protect applied product from inclement weather until fully cured or finish is applied.

For Use As A Foam Trim Adhesive:

1. Apply the Vise Adhesive to the back of the EPS Insulation Board with a 3/8"x3/8"x3/8" (9.5x9.5x9.5 mm) or a 3/8"x1/2"x1-1/2" (9.5x13x38 mm) stainless steel notched trowel.
2. Apply the Vise Adhesive to the back side of the insulation board.
3. Press the trim piece onto the wall at the desired location.
4. Allow the Vise Adhesive to set for a minimum of 24 hours prior to working on the insulation board.

For Use As A Foam Trim Base Coat:

1. Apply Vise Adhesive to the substrate a minimum of 1/16" (3.2 mm) thick.
2. Completely embed Master Wall Inc.® Reinforcing Mesh into the wet skim coat.
3. Trowel smooth, ensuring that no reinforcing mesh color is visible.

Coverage per pail (sf/sm)*

Adhesive & Standard Base Coat:
120 sf (11 sm)

Embedding Single-layer of Mesh:
240-280 sf (22-26 sm)

Notched Trowel Adhesive Application:
135 sf (12.5 sm)

**All coverage is approximate and depend upon substrate, details and individual application*

Packaging/Shelf Life/Storage

Packaging: 5 gallon (19 L) pail

Shelf Life: 2 years

Storage: Protect from extreme heat - 90 °F (32 °C), freezing and direct sunlight.

Area of Use

Vise Adhesive may be applied to the following substrates:

1. Portland Cement/One Coat Stucco
2. Masonry
3. Poured-in-place and/or Tilt-up concrete.
4. Expanded Polystyrene Trim (with Accent Mesh).

Surface Preparation

All surfaces to receive application must be clean, dry and free of debris, dirt and dust, efflorescence, grease, oils, curing agents, paint/coatings and cleaning solutions. Ensure that all surfaces are smooth and free of any irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Cleaning and smoothing may be accomplished by pressure washing, mechanical sanding, scraping, chipping, and/or sand blasting. Smooth or glossy surfaces must be roughened to ensure a proper bond.

CURING AND DRYING

1. Protect applied product from inclement weather until fully cured.
2. Curing and/or drying time may vary due to climactic conditions, but should not take less than 24 hours at an ambient and surface temperature of 70° F (21° C) and 55% R.H. Variations in Ambient and surface temperature and humidity may prolong curing and/or drying time. All freshly applied material must be protected by an approved protective system from inclement weather until fully cured and/or dried.
3. It is the responsibility of the applicator to determine if the product is fully cured and/or dry prior to exposing it to rain, snow, dew, and/or any other inclement weather condition that may be detrimental to the product.

DO NOT apply product when the ambient and surface temperature is below 40° F/4° C or above 100° F/34° C. The ambient and surface temperature must stay consistently within this range until fully cured (see also CURING). Material that is allowed to freeze may suffer irreparable damage. Protect all work from inclement weather with an approved protective system until fully cured.

DO NOT add any other materials to the mixture of the product without written approval from Master Wall Inc.® deviate in the mixing or application procedures contained in this, or any other ACCENT Data Sheets, without written approval from Master Wall Inc.®

Cleaning may be accomplished with water immediately after use.

WARNING, THIS PRODUCT CONTAINS SILICA

If sanding or scraping are performed, ventilate work area and/or use a NIOSH/MSHA-approved respirator in accordance with our Safety Data Sheet.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2026 Master Wall Inc.®

Health & Safety

WARNING!

Causes eye and skin irritation. Precautionary Statement Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Store locked up. Dispose of contents/container in accordance with Local, State, Federal and Provincial regulation.

Spills: Collect with suitable absorbent material such as cotton rags.

Disposal: Dispose of in accordance with local, state or federal regulations.

Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.

Consult the Safety Data Sheet (SDS) in the Products section at masterwall.com for further health and safety information.





PRODUCT DATA

ACCENT MESH

Accent Mesh is a specially woven, glass fiber mesh for reinforcing stucco surfaces and as a reinforcement for foam shapes used with stucco. Accent mesh improves stucco crack resistance when embedded into Accent Base Coats as a leveling and reinforcement component.

APPLICATION PROCEDURE

Job Conditions - Air and substrate temperature for embedment of the Reinforcing Mesh must be 40°F (5°C) or higher and must remain 40°F (5°C) or higher for a minimum of 24 hours. Provide temporary protection at all times until the wall system, including flashings, caps, and sealants, is completed to provide protection from climatic conditions and other potential damage.

Application - Apply the base coat over the entire surface of the stucco in a thickness greater than that of the Accent Mesh being used, approximately 1/16" (1.6 mm). Immediately embed the Accent Mesh into the wet base coat and smooth from the center to the edge to avoid wrinkles. Lap mesh a minimum of 2-1/2" (63.5 mm) on all sides. The reinforcing fabric must be continuous at all corners and lapped or abutted. The overall minimum thickness of the base coat should be a nominal 1/16" (1.6 mm) when dry.

- Apply in a similar manner over foam shapes used in stucco.
- For inside and outside corners when using Accent Base Coats, the mesh may be lapped up to 12" (305 mm) on each side.
- Apply in a similar manner when embedding into wet stucco brown coat as an external reinforcement without leveling base coat.
- Accent Mesh is intended only for this specific stucco application and not approved for other Master Wall® system applications.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2026 Master Wall Inc.®



Mesh Weight & Coverage*

Weight: 4.4 oz/sy (156 g/sm)

Roll Size: 38" x 150' (96.5 cm x 45.7 m)

Coverage per Roll: 475 sf (44.1 sm)

**All weight and coverage is approximate and depend upon substrate, details and individual application*

Packaging/Storage

Packaging: 4 Rolls per Box

Storage: Keep dry, protect from extreme heat - 90°F (32°C), and direct sunlight.

LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.



Accent Stucco Products

5 Year Limited Warranty

Master Wall Inc.® warrants the properly designed and installed Master Wall Inc. materials for 5 years from the date of installation. Master Wall Inc.'s exclusive liability under this warranty is to supply replacement materials, if it is shown that the materials supplied by Master Wall Inc., were defective when installed by the Master Wall Inc. certified applicator. Remedies shall be solely determined by Master Wall Inc. and no other warranties are expressed or implied. For a valid warranty, the system and products must be installed in accordance with Master Wall Inc.'s written recommendations, specifications, details, bulletins and other project-specific written recommendations. Master Wall Inc. must be notified in writing within 30 business days of the original discovery of the defect.

Master Wall Inc., is not responsible for structural conditions, design conditions beyond those noted in our literature, architecture, engineering or workmanship of any project. This warranty does not cover failures or defects which are due to the failure on any building component, materials not manufactured or sold by Master Wall Inc. This warranty does not cover failures or defects resulting from improper installation of the products or workmanship, improper storage, abuse, vandalism, damage from accidental causes or negligence by any person, thermal movement, structural movement, structural failure, acts of God, engineering or design deficiencies, or defective or insufficient caulking.

Abuse, misuse, excessive weather or environmental conditions beyond what the products or systems have been tested, designed or approved for is expressly limited. Certain colors with organic pigments are less fade-resistant than others. The building, system and products must be properly maintained in accordance with Master Wall Inc., documents, local environmental conditions and good building practices. In no case is Master Wall Inc. responsible for incidental and consequential damages.

This warranty becomes effective only when all bills for the components of the system have been paid.

Except as stated, Master Wall, Inc., expressly disclaims any warranty of merchantability or fitness for a particular purpose. The above remedies are to be deemed exclusive.

Project:

Applicator:

Warranty Date:

***This is not the final warranty.
For a valid warranty fill out a
warranty request under Tools
and Technical at
masterwall.com. Warranties
are not valid until issued.***